



Creating Security Solutions.
With Care.

riscogroup.co.uk

Novagard Active

Sounders

CPX control panel

Local Adaptor

2K (not with EOL) 12v 1.2A, 2.0A, 3.0A, 7.0A 150mA @ 12VDC

8 (2-wire), 9(EOL) or 8+8(EOL)

CPX Control Panel, LCD Proximity Keypad

CP8L LCD Control Panel c/w LCD Keypad

LCD Control Panel c/w LCD Keypad Grade 2 version

CPX LCD RKP option for proximity

e-reader (External) Setting White i-reader (Internal) Setting White

e-reader (External) Setting Brown

230 VAC

195x250x80

118x90x24

CPX Control Panel

CP8L LCD Keypad

CPX Demo Kit

G-Tag Keyfob

Remote Software Program Transfer Module CP8L

50mA

195x250x80

118x90x24

2K

8

230 VAC

1.2A, 2.0A, 3.0A, 7.0A

Wireless

Expansion

Communication

Technical Specifications CPX

Voltage Input

No. of zones

Control Panel

KITCPX

EW021

EW023

KITCP8L

01153

01155

01156

01157

01107

77023

CPXDEMOKIT

EW002LCDG2

KITCP8LG2

Max Loop Resistance

Battery Sizes (Ah)

Quiescent current

Dimensions (mm)

Dimensions (mm) keypad

Ordering Information

Upload/Download

compatible



VG-TAG

- Up to 4 LCD remote keypads can be added
- Alert keys for PA/Fire on keypad
- G-Tag compatible for proximity set/unset via the G-Tag keyfob
- Using Micro Maglock and Z Bracket complies with ACPO DD243 requirements for single room applications

Wireless Accessories (CPX)

- Wireless PIR and PET PIR
- Universal Transmitters and Door/Window Contact
- Wireless Shock, Smoke, Flood and Glassbreak detectors
- 2 button Panic keyfob / 4 button keyfob
- Wireless WatchOUT Outdoor Detector

Remote Upload/Download (CPX)

- GT Remote allows full remote management according to user authority
- Novagard Active compatible; Engineer can remotely diagnose and control external sounder parameters to guarantee continued operation
- Complete system can be tested by master user

Communication (CPX)

- Digi modem onboard communicator for signaling and complete remote system management
- ARC signalling using Contact ID, SIA or Ademco FF formats
- Vo-comm: Up to 4 phone numbers with preprogrammed message Advanced GSM/GPRS Communication with RISCO
- Group's Universal AGM

External Sounders (CPX)

- Novagard Active compatible for remote diagnostics
- Wide range of cover & lens colour combinations
- Customized Screen printing available Separate bell tamper to detect compromise of
- the external sounder

Program Transfer Module (PTM) (CPX)

- Copy installation defaults from master system to other systems
- Save backup of installation program

CP8L Features

- PD6662 EN-50131-1 Grade 2X
- Up to 4 LCD RKPs can be added
- 8 fully programmable zones
- 9 user codes & 250 log event memory time & date stamp
- Engineer code lock in, Service timer & Anti-code
- Individual tamper indicators (not zones)
- Two part sets (optional silent part)
- Programmable alert keys PA, Fire or Alert
- Programmable chime function (any zone)

The CPX is compatible with the Intamac 'Home Manager' automated alarm monitoring & messaging service.







Approved for ISO 9001-2000







riscogroup.co.uk

RISCO Group UK Ltd. Commerce House, Whitbrook Way Stakehill Distribution Park, Middleton, Manchester, M24 2SS Phone: 0161 655 5500, Fax: 0161 655 5501, e-mail: sales@riscogroup.co.uk