

Technical Specifications

The Enforcer is a fully two way wireless control panel from Castle, using wireless devices by Pyronix. The Enforcer boasts a number of features including:

- Two Way Wireless Technology
- One Push to Learn
- Friendly Programming Menu
- Signal Strength Indicator
- Two Way Wireless Diagnostics



Maximum Inputs

Wireless	32
Wired	2 (DEOL)

Outputs

Output Modules	1
On Board Outputs	3
Maximum Outputs	19

Set/Unset

Keypad	In-built
Prox Reader	In-built
Additional keypads	Max 3
User Codes/Prox	80
Wireless Keyfobs	32
Levels	4

System Logs

Event Memory	750
--------------	-----

Remote Signalling

RS232 Port	UDL
PSTN DigiModem	SMS, Fast Format, CID, SIA-3, ARM, UDL

Gradings

EN50131-3 : 2009
EN50131-6 : 2008
EN50131-5-3 : 2005
Security Grade 2
Environmental Class II

Physical Characteristics

Dimensions	220 x 160 x 50mm
Weight	1025g
Operating Temperature	-10°C to +40°C
Storage Temperature	-20°C to +60°C

Power Supply

Quiescent Current	80mA
Alarm Current	350mA
Quiescent Current (with battery charge)	250mA
Available Aux Current	166mA
Battery Backup	12 hours