



# HomeControl+ Cameras



Compatible with  
PyronixCloud & HomeControl+



# HomeControl+ Cameras



The plug-and-play IP camera solution brings remote home monitoring to a new level, with real time streaming over IP communications directly to your HomeControl+ App.

Whether it is internal or external monitoring that is required, the HomeControl+ cameras will meet your user's needs. The range consists of a static external camera, and a pan and tilt internal camera which provides 340° horizontal and 90° vertical surveillance. Both cameras include HD streaming in 720p quality over WiFi or LAN connections.

The cameras are compatible with the HomeControl+ App, operated through the PyronixCloud and HomeControl+ infrastructure.



		I-CAM/PT	X-CAM/S
Characteristics		Internal Pan and Tilt Camera	External Static Camera
Image sensor	Sensor	High Definition Colour CMOS	High Definition Colour CMOS
	Max. resolution	1280 x 720 (1 Mega-pixel)	1280 x 720 (1 Mega-pixel)
	Min. illumination	0.1 Lux (with IR Illumination)	0.1 Lux (with IR Illumination)
Lens	Focal length	f:3.6mm	f:3.6mm
	Aperture	F1.8	F1.8
	Angle of view	71°	71°
Video	Resolution	720p	720p
	Compression	H.264	H.264
	Frame Rate	25fps (max.)	25fps (max.)
	Pan/Tilt Angle	Horizontal: 340° e Vertical: 90°	None
	Infrared LED	10 LED IR	30 LED IR
	Night vision range	8 m	15 m
Audio	Microphone	Integrated microphone	No
Network	Ethernet	LAN 10/100Mbps	LAN 10/100Mbps
	WIFI	IEEE802.11b/g/n (WEP, WPA, WPA2)	IEEE802.11b/g/n (WEP, WPA, WPA2)
System requirement	HomeControl+ APP	iOS, Android	iOS, Android
SD Card	Max 32GB	SD recording	No
Power	Power supply	5Vcc/2.0A	12Vcc/1.0A
	Current consumption	7.5 W (Max.)	6.9 W (Max.)
Environment	Water proof	No	IP 66
	Operating temperature	(-20° ~ 55°C)	(-20° ~ 55°C)
	Storage temperature	(-20°C ~ 60°)	(-20°C ~ 60°)
	Humidity	0% ~ 90%	0% ~ 90%
Others	Dimensions (h x w x d)	200/180/120 mm	199.5/169.5/112 mm
	Certifications and guarantee	CE, RoHS. 1 Year	CE, RoHS. 1 Year